

36" Ride-On Roller — 1.5 Ton (Petrol)

Air-Cooled Petrol Engine · Hydrostatic Transmission · CE Certified



A 1.5-tonne petrol ride-on roller with a 1000 mm (36") rolling width, built for cricket squares, tennis courts and fine turf. An air-cooled petrol engine drives a fully hydrostatic transmission for smooth, infinitely variable speed in both directions, while hydraulic power steering and a non-articulated front-wheel drive give tight, clean turns without scuffing the surface. Electric key start, a fitted canopy and head light make it easy to run day to day, and an optional 250–300 kg ballast adds compaction when needed.

SPECIFICATIONS

Model	1.5 Ton Hydrostatic Roller – CE Certified, Petrol Engine, Key start
Operating weight	1500 Kgs
Engine	Air-cooled petrol engine
Transmission	Hydrostatic, variable speed on reverse and forward
Rolling width	1000 mm (36")
Over-all width	1100 mm
Over-all length	2460 mm
Over-all height	1380 mm (2070 mm with canopy)
Speed	0–6 kmph
Hydraulic oil	45 Litre tank capacity
Wheel size	Rear – Dia 600 x 1000 wide; Front – Dia 600 x 1000 wide
Steering	Hydraulic power steering
Steering wheel drive	Front-wheel non-articulated drive for smooth turn & finish
Starting	Electric start (ignition switch)
Battery	Heavy duty 12 Volt
Head light	Yes
Chassis	Single chassis body design, with front wheel pivoted to chassis
Feature	Manual push or pull allowed during major failure
Canopy	Yes
Chain tension idler	Yes
Acceleration	Hand-operated ratchet control, push-button release
Reverse / forward	Manual hand control lever
Ballast option	250–300 kgs available